

MUTCD RADIUS CORNER  
(1 7/8" RADIUS)

30"

0.5"

0.5"

# EROSION/SEDIMENT CONTROL ZONE

2" LETTERS  
1 1/2" SPACING


KEEP STREETS CLEAN

MUDDY WATER DISCHARGE  
PROHIBITED

1 1/2" LETTERS

KEEP EXPOSED SOIL TO A MINIMUM  
STORING CONSTRUCTION MATERIALS  
ON STREET PROHIBITED

36"



(AMC TITLE 12)

FOR INFORMATION CONTACT:

CITY OF ALBANY

ENVIRONMENTAL SERVICES DIVISION

1" LETTERS

**917-7600**

2" LETTERS

1. THE EROSION AND SEDIMENT CONTROL SIGN SHALL BE 30" WIDE BY 36" HIGH. THE SIGN MATERIAL SHALL BE ANODIZED ALUMINUM WITH A THICKNESS OF 0.08".
2. LETTERING SHALL BE UPPER CASE ENGINEER'S GRADE WHITE ON GREEN BACKGROUND WITH 1/2" WHITE BORDER.
3. CITY OF ALBANY LOGO BOX MEASURING 8" BY 10", SHALL BE LOCATED IN THE LOWER LEFT CORNER INSET FROM THE WHITE BORDER.
4. DISTANCE FROM GROUND TO THE BOTTOM OF THE SIGN SHALL BE 7'
5. THE SIGN SHALL BE ATTACHED TO A 2 3/8" O.D. GALVANIZED STEEL POST WITH A WALL THICKNESS OF 0.95".
6. THE POLE BASE SHALL BE A V-LOCK BASE, 30" 23 VR3 AS MANUFACTURED BY FORESIGHT PRODUCTS, INC. OR APPROVED EQUAL.
7. SIGNS SHALL BE LOCATED PER THE CITY ENGINEER'S DIRECTIVE.
8. SIGNS SHALL BE ATTACHED TO POLES WITH 2 SINGLE CLAMPS ON U BRACKETS FOR 2" I.D. PIPE WITH HEX HEAD CAP SCREWS.

CITY OF ALBANY, OREGON  
PUBLIC WORKS DEPARTMENT

EROSION SEDIMENT CONTROL  
SIGN

NO SCALE

MARCH 2008

NO. 211